POSC09150A

POSC09150A 9V/1.5A/13W, adapter czarny, gniazdo AC:CEE 7/16. wtyk 2.1x5.5mm prosty



ELECTRICAL SPECIFICATION

Housing type	Wertykalny
Output Voltage	9V DC
Rated Current	1.5A
Power (W)	13
Dimming	No
Voltage Ripple & Noise (max.)	200mVP-P
Line Regulation	± 5%
Load Regulation	± 5%
Setup, Rise Time	100ms / 230VAC
Hold up Time (typ.)	3ms / 230VAC
AC input voltage range	Universal
Protection class	II
Efficiency (typ.)	83.59%
AC Current (typ.)	0.6A
IP protection level	IP20
Over Current / Overload protection (range)	1.65A-2.7A
Over Current / Overload protection	Type: auto-recovery.
Short Circuit protection	Type: hiccup mode, auto-recovery.
Over Voltage protection	Close output, recovers automatically after fault removed
Working Temperature range	-5°C ÷ +40°C
Working Humidity range	5 ÷ 95% RH

2026-10-08

Storage Temperature and Humidity	-40°C ÷ 85°C, 5 ÷ 90% RH
Withstand Voltage	IN/OUT: 3.6kVAC
Isolation Resistance	IN/OUT: 50MΩ/500VDC/25°C/70%
EMC Emission	EN55032, EN61000-3-2, EN61000-3-3
Harmonic Current	EN61000-3-2, EN61000-3-3
Dimmensions (L x W x H)	56x28x42mm
Weight (kg)	0.073
Warranty	2 years
Mounting	Wall mounted
DC Plug	2.1/5.5 mm
Programmable	No

MECHANICAL SPECIFICATION